

# LINX 8820 PRINTER



**The Linx 8820 continuous ink jet printer prints up to 3 lines and provides a perfect coding solution for industrial environments.**

Designed to reduce your total cost of ownership and increase your production line output, the Linx 8820 delivers consistent, error-free codes.

With its unique sealed printhead design and durable stainless steel construction the Linx 8820 operates reliably in tough production environments, optimising line productivity.



Self Service  
Module with  
Interval  
12 months

## Low total cost of ownership

- ✓ Solvent consumption as low as 3.5ml\* per hour to save on fluid costs
- ✓ Single part ink and filter change minimising service costs
- ✓ Printhead cleaning interval up to three months to reduce downtime and fluids consumption



# Pump  
Warranty for  
10 years or  
50,000 Hrs

## Built-in reliability for increased productivity

- ✓ Unique sealed printhead design protects critical components from physical damage
- ✓ 8 hour reserve print capacity to reduce line stoppages from fluid running empty
- ✓ Linx PrinterNet™ enabled IoT solution gives you better control of your production line and fast remote fault resolution to improve uptime



Seasonal  
shutdown  
without  
flushing

## Consistent error-free codes and ease of use

- ✓ Customisable touch-screen with your product images to provide error-free code setup without language barriers
- ✓ Fast one-touch access to frequently used functions and step by step guides for right first time set up
- ✓ Simple, one-touch, fluid cartridge refills during printing no mess, no tools, no mistakes

\*average consumption at 20°C, ink and application dependent  
# Pressure Pump

**PRINthead**

60mm minimum bend radius in static applications. 180mm minimum bend radius in dynamic applications.



**SIDE ELEVATION**



**FRONT ELEVATION**



**90° PRINthead OPTION**



**Technical Specifications**

**PRINT SPEEDS AND SIZES**

Printhead:	Mk11 Midi	Mk11 Midi plus
Nozzle size:	62 µm	75 µm
Lines of print:	Up to 3	Up to 3
Character height range:	1.8 to 20 mm	2.1 to 20.1 mm
Maximum speed for single line print (5 dot high characters):	6.25 m/s (0.47 mm drop pitch)	7.28 m/s (0.57 mm drop pitch)
Maximum speed for two line print (7 dot high characters):	2.46 m/s (0.43 mm drop pitch)	2.38 m/s (0.52 mm drop pitch)
Recommended distance from printhead to substrate:	12mm (35mm for carton coding message style)	20mm (45mm for carton coding message style)

**HARDWARE FEATURES**

- Easi-Change® Service Module, change interval: up to 12 months (6,000 hours) – dye-based inks, up to 12 months (6,000 hours) – soft pigmented inks\* Only 0.5L of ink changed
- Unique automatic printhead flushing: typical cleaning interval 3 months (100 starts and stops) – dye-based inks, up to 1 month – soft pigmented inks
- Printhead jet-speed control and temperature sensing for consistent printing in changing ambient temperatures
- Mistake-proof, mess-free ink and solvent refilling while printing (0.5 litre ink cartridge, 1 litre solvent cartridge)
- 7-inch full colour touch screen with tough, solvent-resistant polymer cover
- Durable ink pump with no scheduled changes required
- Extended shutdowns (up to 3 months) without printer flushing or draining
- Robust, flexible dual-tube conduit for static and moving printhead applications

**SOFTWARE FEATURES**

- Single-press start print, pause print and jet shutdown
- Auto power-off after jet shutdown
- Simple message creation and editing with drag-and-drop field positioning, zoom function and insert mode for long messages
- Total print count, message count and batch count
- Message selection using product images
- Password-protected functions, with customisable user profiles
- Message creation/editing while printing
- On-screen output rate measurement and production stoppage log. Downloadable onto USB device

- On-screen fluid level indicators, 12 hour running from fluid refill warning to printer stop in most applications
- On-screen help and diagnostics information
- PrintSync® automatic font and message format selection, based on message style selected and production line speed
- Multiple operator languages (user selectable) with on-screen keyboards, secondary keyboard for multi-language printing
- Simple line speed and shaft encoder setup wizard, for installation on new production lines
- Message store and printer settings backup, copy and restore using USB storage device
- Simple Communications Protocol (YAML based scripts) and Linx Remote Communications Interface for connection to PCs or PLCs using Ethernet port

**MESSAGE PRINTING FACILITIES**

- Text, symbols and numbers
- Prompted fields for one-step message editing with customisable on-screen prompts
- Height, width and delay functions for easy code sizing and positioning
- Automatic formats for printing dates, times and date rounding (using the printer's internal clock)
- Automatic date forward function. Add number of seconds, minutes, hours to the current time, or number of days, weeks or months to the current date
- Automatic time adjustment option for daylight savings time
- Sequential numbering, forward and backward counting, variable intervals
- One-touch sequential number reset option from the printer screen, and reset using external trigger
- Number of messages stored: up to 1000 using internal printer memory (depending on message content), more can be stored using a USB storage device
- Bold character printing (up to 9 times)
- Variable character spacing and inverse image printing, for improved readability and vision system recognition
- Rotated character (tower) printing
- Shift coding (message content changes automatically at defined times)
- Graphics and logos can be imported into the printer as bitmap files using the USB port
- Inverse image printing

**PRINthead OPTIONS**

- 2m conduit
- 4m conduit (option)
- 90° printhead (option)
- Positive air purge to printhead (provides improved reliability in dusty or humid environments) (option)
- Air dryer (provides improved reliability for certain inks at high humidity and temperature) (option)

**INK RANGE**

- Linx MEK base (dye-based, soft pigmented-based)
- Linx mixed base (MEK-free, dye-based)
- Linx ethanol base (MEK-free, dye-based)

**SOLVENT CONSUMPTION**

3.5ml/hour (at 20°C, ink and application dependent)

**CONNECTIONS/INTERFACING FOR**

- Product detector
- Shaft encoder/second product detector
- External single-stage alarm output (24v)
- USB – for message backup and transfer, and wifi connection for Linx PrinterNet
- Ethernet
- Volt-free contact alarm connection (e.g. for use with external mains-driven alarm) (option)
- Dual alarm output (Volt free and 24V output) (option)

**PHYSICAL CHARACTERISTICS**

- Base and enclosure: Stainless steel
- IP55 environmental protection rating\*\*
- Mounting options: Static stand, mobile stand, bench, wall mount bracket
- Operating temperature range: 5-45°C (0-50°C for Linx 1240 ink type)
- Humidity range (r.h., non-condensing): 90% max
- Power supply: 100-230V, 50/60Hz
- Power consumption: 38W (typical when printing)
- Power rating: 100 W
- Weight: 24kg (including fluids and printhead)

**REGULATORY APPROVALS**

- CE, EAC, NRTL, FCC
- \*Interval may be adjusted in certain environments and applications to provide reliable running between service module changes
- \*\*IP rating is independently verified – certificates available on request



**PRINT JET SOLUTIONS LLP**

#22, Huliappa Arcade, 2nd Floor, 2nd Block, Nagarbhavi 2nd Stage, Bangalore-72

Contact : +91 8861588815, +91 9035009345, +91 80 29773733

Email : info@printjetsolutions.in Web : www.printjetsolutions.in

•HYDERABAD •CHENNAI •KOCHI •VISHAKAPATTANAM •MYSORE •COIMBATORE •CHITTOOR •HUBLI.

